



**SPECIFICATIONS:**

- 1.RATING:11V AC 1A MAX  
OR 12V DC 2A MAX.**
- 2.INSULATION RESISTANCE:  
50M OHM MIN AT 500V DC.**
- 3. DIELECTRIC STRENGTH:  
500V AC / 1 MINUTE.**

**MATERIAL:**

- A.COVER: PE+2L**
- B.SHELL: ABS**
- C.METAL SHIELD:  
BRASS NICKEL PLATED**
- D.HOUSING: NYLON66+GF**
- E.CONTACT:  
BRASS SILVER PLATED**

RoHS Compliant		<b>HSM</b> 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 <b>BETTY</b>	SCALE 比例 参考	TOLERANCE 容許公差 .0 ± .00 ± ANG. ±	PART NAME 品名 MINI DIN ASSEMBLY TYPE XXP MALE NICKEL SHELL MACHINED PIN SILVER PLATING
DWG. 製圖 <i>Jolin</i>		UNIT 單位 MM	SIZE. 紙張尺寸 A4
DATE 制表日 2007/03/16	PAGE 張數 1 OF 1	REV. 版次 A	PART NO. 料號 C8011-XXMBVB 00R